



NOTES:

1. DETAIL IS FOR SINGLE POST SIGNS.
2. ALL DIMENSIONS IN MILLIMETRES UNLESS OTHERWISE NOTED.
3. HORIZONTAL CLEARANCES BASED ON DESIGN SPEEDS UP TO 60 km/h AS PER SECTION 4.15 IN BYLAW 7900. FOR HIGHER SPEED ROADS REFER TO TAC TRANSPORTATION ASSOCIATION OF CANADA ROADSIDE DESIGN.
4. SIGN SLEEVE TO BE PLACED PRIOR TO SIDEWALK POUR, OR TO BE CORED IN AFTER. FOR EXISTING SIDEWALK CORE MINIMUM 125mm HOLE IN SIDEWALK, SUB-EXCAVATE AND FILL WITH CONCRETE AROUND SLEEVE.

CONCRETE BASE					
APPLICATION	A mm	B mm	C mm	APPROX. MASS	VOLUME OF CONCRETE
GRAVEL SHOULDER OR HIGHWAY	305	203	584	85 kg	0.05m ³
PAVED SHOULDER OR LANDSCAPE	229	152	457	37 kg	0.02m ³

**STANDARD
DETAIL
DRAWING**

DATE:
OCT 31/22
SCALE:
NTS

POST MOUNTED SIGN

DWG. NO.

SS-R61

